CONSTRUCTION HOUSEKEEPING CHECKLIST

	Date					
	Location					
Completed by						
OK = Satisfactory AN = Action Needed N/A = Not Applicable OK AN N/A						
1	Work areas, passageways, and stairs are clear of debris, including lumber with protruding nails. [1926.25(a)]					
2	Combustible scrap and debris is safely removed from the worksite at regular intervals during construction. [1926.25(b)]					
3	Waste containers are provided to collect and separate trash, oily and used rags, and other debris. [1926.25(c)]					
4	All solvent waste, oily rags, and flammable liquids are kept in fire resistant covered containers until removed from worksite. [1926.252(e)]					
5		uction areas, ramps, walking areas, stairways, storage areas, work areas are adequately illuminated. [1926.56]				
6	An adequate supply of potable water is provided. [1926.51(a)(1)]					
7	An adequate number of toilets are provided. [1926.51(c)]					
8	For workers engaged in the application of paints, coating, herbicides, or insecticides, or in other operations where contaminants may be harmful, adequate washing facilities are provided and maintained in a sanitary condition. [1926.51(f)]					
9	Permanent work locations have adequate bathroom facilities with running water, hand soap, and hand towels or an air blower. [1926.51(f)(3)]					
10		do not eat or drink in any areas where toxic materials are [1926.51(g)]				
11		work areas are maintained to keep out rodents, insects, and min. [1926.51(h)]				



CONSTRUCTION HOUSEKEEPING CHECKLIST

OK =	= Satisfactory AN = Action Needed N/A = Not Applicable	OK	AN	N/A
12	If rodents, insects, or pests are found in the work area, a continuing and effective extermination program is initiated. [1926.51(h)]			
13	Storage areas do not create additional hazards and materials are secured in a way to ensure that they won't slide, fall, or collapse. [1926.250(a)(1)]			
14	Aisles and passageways are kept clear and in good repair to ensure equipment and workers can move through safely. [1926.250(a)(3)]			
15	Storage areas are maintained to ensure there are no tripping, fire, explosion, or pest hazards. [1926.250(c)]			
16	An enclosed chute is used when materials are dropped more than 20 feet to any point outside the building. [1926.252(a)]			
17	When debris is dropped through holes in the floor the lower level is barricaded, and warning signs are posted. [1926.252(b)]			
18	As work progresses, all scrap lumber, waster material, and rubbish is removed from the immediate work area. [1926.252(c)]			
19	Stairways have no hazardous conditions like protruding nails or slippery conditions. [1926.1052(a)]			
20	While cleaning, if combustible dust is a potential hazard, vacuuming and non-vigorous sweeping are used in place of blowing down with compressed air.			
21	When it is necessary to blow down in place of vacuuming and sweeping, compressed air pressure is limited to 30 psi, and dust clouds are kept to a minimum. [1926.302(b)(4)]			
22	Exit routes are not obstructed by materials or equipment, even temporarily. [1926.34]			
23	Sufficient access and working space is maintained around all electrical equipment. [1926.403(i)(1)]			

Add notes on the following page.



CONSTRUCTION HOUSEKEEPING CHECKLIST

Action Needed Items and Additional Notes:						

This document may not be comprehensive for the requirements of the workforce or facility being evaluated. Weeklysafety.com does not assume liability for damage or injury presumed to be caused by use of this document. Use of this document does not guarantee conformity with any laws or regulations, nor does it ensure absolute workplace safety.

