

SAFETY MEETING QUIZ

Name:

Date:

Safety Topic: V2-14 Site Safety – Machine Guarding Hazards

1. Machine guards are critical to the safety of workers.
 - a. True
 - b. False

2. OSHA Standard 1910.212(a)(1) states that one or more methods of _____ shall be provided to protect the operator and other employees in the machine area from hazards such as those created by point of operation, ingoing nip points, rotating parts, flying chips and sparks.
 - a. respiratory protection
 - b. PPE
 - c. machine guarding
 - d. fall protection

3. Recognizing the potential hazards of machines starts with understanding the first place where the potential for injury exists which is called the
 - a. hands off area.
 - b. point of operation.
 - c. tool box.
 - d. break room.

4. Workers have to be protected from _____ that pose a danger to the operator.
 - a. point of operation hazards
 - b. power transmission apparatus such as pulleys and chains
 - c. moving or rotating parts
 - d. all of the above

5. Guarding shall be designed and constructed as to **prevent the operator** from having _____ during operation.
 - a. to wear PPE
 - b. to do much work
 - c. any part of his body in the danger zone
 - d. a clean work environment



SAFETY MEETING QUIZ

ANSWER KEY

Safety Topic: V2-14 Site Safety – Machine Guarding Hazards

- Machine guards are critical to the safety of workers.
 - True
 - False
- OSHA Standard 1910.212(a)(1) states that one or more methods of _____ shall be provided to protect the operator and other employees in the machine area from hazards such as those created by point of operation, ingoing nip points, rotating parts, flying chips and sparks.
 - respiratory protection
 - PPE
 - machine guarding
 - fall protection
- Recognizing the potential hazards of machines starts with understanding the first place where the potential for injury exists which is called the
 - hands off area.
 - point of operation.
 - tool box.
 - break room.
- Workers have to be protected from _____ that pose a danger to the operator.
 - point of operation hazards
 - power transmission apparatus such as pulleys and chains
 - moving or rotating parts
 - all of the above
- Guarding shall be designed and constructed as to **prevent the operator** from having _____ during operation.
 - to wear PPE
 - to do much work
 - any part of his body in the danger zone
 - a clean work environment

